




Pos.	Qty.	Description	Data sheet	Remarks.
1	(i)	Cable, Cat.7, S/FTP 4x2x26AWG/7, FRNC, blue	Belden 74005NH	
2	1	End A: IDC Connector ix, type B	HRS: IX30G-B-10S-CV (7.0)	acc. to IEC 61076-3-124
3	1	End B: IDC Connector ix, type B	HRS: IX30G-B-10S-CV (7.0)	acc. to IEC 61076-3-124

For technical data of cable and/or connector please refer to their data sheets.



End A

Wire map acc. to TIA/EIA 568B (Contacts 3 & 8 not connected)		
1	orange / white	1
2	orange	2
4	blue	4
5	blue / white	5
6	green / white	6
7	green	7
9	brown / white	9
10	brown	10
	shield	



End B

Transmission support	
Category	ISO/IEC 11801 Cat.6A
1/10 GBs	IEEE 802.3ab/IEEE 802.3an
Electrical data	
Rated voltage / current	50 V AC / 60 V DC / 1 A
Contact resistance	30 mΩ
Mechanical data	
Operating temp.	-40 °C to +80°C
Mating cycles	5000
Crimp strength	> 60N
RoHS	Compliant

L [m]	SB PN	MOQ
0.1	154906	1
0.2	154907	1
0.5	154908	1
1.0	154909	1
2.0	154910	1
5.0	154911	1
10.0	154912	1

THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF SINBON ELECTRONICS CO., LTD. IT MAY NOT BE USED OR ITS CONTENTS COPIED OR DISCLOSED TO A THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT AND IS TO BE RETURNED PROMPTLY UPON REQUEST BY SINBON ELECTRONICS CO., LTD.			
CUSTOMER P/N :		REV. A	
TOLERANCE :		DRA. 01-03-2018	
< 100 mm: +5 mm 101~200 mm: +10 mm 201~500 mm: +10 mm 501~1000 mm: +10 mm 1001~2000 mm: +20 mm 2001~5000 mm: +50 mm 5001~10000 mm: +100 mm		Róbert Huszti CHK. 12-03-2018 Attila Mészáros APR.	
CUSTOMER :		SINBON SINBON Electronics Co., Ltd.	
DESCRIPTION :		High Speed ix Industrial Patch Cable ix type B - ix type B	
PART NUMBER :		9001111###-72R/82	
REV. 01		SIZE A3 UNIT mm SCALE NONE SHEET 1 of 1	